

Amendments to the Claims:

Please amend the claims as set forth below.

1. (Currently Amended) A Hheadlamp for vehicles comprising:
at least one planar luminous panel having a plurality of luminous-element chips;
an optical element arranged in the beam path of the light beam emitted by the luminous panel;
the luminous-element chips (4) of the luminous panel (3, 21, 31) being arranged in a common recess (5);
the recess (5) being on one side facing in the direction of light emission (8);
an edge (9, 25, 32), the edge being in a spatial arrangement to the luminous-element chips (4) such that a predetermined luminance gradient (G, G', G'') in a light distribution (L) of the headlamp is formed in the region of the edges (9, 25, 32).
2. (Currently Amended) A Hheadlamp according to claim 1, wherein the recess (5) is trough-shaped with an edge wall (7, 7', 7'') which runs perpendicularly to the direction of light emission (8) of the luminous panel (3) and stands up from a bottom side (6) of the recess (5) and on whose side facing away from the bottom side (6) runs the edge (9).
3. (Currently Amended) A Hheadlamp according to claim 1 wherein the edge (9) runs peripherally in a plane which is oriented perpendicularly to the main direction of emission of the luminous panel (3).
4. (Currently Amended) A Hheadlamp according to claim 1 wherein the shape of the edge wall (7, 7') and/or edge (9) is such that, in combination with the optical element (2, 23, 34) mounted in front, a predetermined luminance distribution is produced.
5. (Currently Amended) A Hheadlamp according to claims 1 wherein the edge wall (7, 7') and/or the edge (9) of the recess (5) has a rectangular or triangular or

circle segment shape in a top view, and in that the edge (32, 32') has a break (33) for forming an asymmetrical light/dark boundary (LDB).

6. (Currently Amended) A Hheadlamp according to claims 1 wherein several light-emitting diode chips (4) are arranged directly adjoining at least the edge wall (7, 7') comprising the edge (9) which produces the light/dark boundary (LDB).

7. (Currently Amended) A Hheadlamp according to claims 1 wherein the recess (5) is filled with a light-converting luminescent material, such that the light emitted by the luminous-element chips (4) is converted to white light.

8. (Currently Amended) A Hheadlamp according to claims 1 wherein ~~the~~ a light-converting luminescent material is integrated in a cast material which covers the recess (5).

9. (Currently Amended) A Hheadlamp according to claims 1 wherein ~~the~~ a bottom side (6) of the recess (5) is reflectively coated.

10. (Currently Amended) A Hheadlamp according to claims 1 wherein the planar luminous panel (3) is integrated in a luminous plate (1), the recess (5) being set in a front side (10) of the luminous plate (1), the front side running perpendicularly to the direction of light emission (8).

11. (New) A headlight for a vehicle comprising:
a luminous element chip having a perimeter and a first extent in a direction of illumination;
a luminous panel, said luminous element chip being within a recess of said luminous panel, said luminous panel having an edge;

said edge having a portion at a second extent in the direction of illumination, said second extent being further from a base portion of said luminous panel than said first extent; and

said edge of said housing having a portion in a first spaced relation with said perimeter of said luminous panel and said edge having at least one other portion in a second spaced relation with said perimeter.

12. (New) The headlight of claim 11 wherein said luminous panel is a triangle.

13. (New) The headlight of claim 11 wherein one of said first or second spaced relations of said edge with said perimeter is substantially adjacent.

14. (New) The headlight of claim 11 wherein said first spaced relation of said housing edge with said perimeter causes a first luminous gradient and said second spaced relation of said edge with said perimeter creates a second luminous gradient.

15. (New) A vehicle headlight comprising:
a luminous element chip having a perimeter and an extent in a direction of illumination;
a luminous panel having a base for attachment of said luminous element chip and said luminous panel having recess with an edge;

said edge having a first portion in a first spaced relation with said perimeter and extent of said luminous element chip such that a first luminous gradient occurs in association with said first portion; and

said edge having a second portion in a second spaced relation with said perimeter and said extent of said luminous element chip such that a second luminous gradient occurs in association with said second portion.